

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ECOFOAM ADVANCED

Product code: AF8196

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Cleaning of animal accomodation and associated equipment

1.3. Details of the supplier of the safety data sheet

Company name: Kilco (International) Ltd
Broomhouses 2 Industrial Estate
Old Glasgow Road
Lockerbie
DG11 2SD
United Kingdom

Tel: +44 (0) 157 620 5480

Email: sds@kilco.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 207 858 1228

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: C: R35

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe burns.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion



Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

SAFETY DATA SHEET

ECOFOAM ADVANCED

Page: 2

contact lenses, if present and easy to do. Continue rinsing.

P405: Store locked up.

P501: Dispose of contents/container to hazardous or special waste collection point.

Label elements under CHIP:

Hazard symbols: Corrosive.



Risk phrases: R35: Causes severe burns.

Safety phrases: S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28: After contact with skin, wash immediately with plenty of water.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S60: This material and its container must be disposed of as hazardous waste.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE

| EINECS | CAS | CHIP Classification | CLP Classification | Percent |
|-----------|---------|---------------------|--------------------------------------|---------|
| 200-573-9 | 64-02-8 | Xn: R22; Xi: R41 | Acute Tox. 4: H302; Eye Dam. 1: H318 | 10-30% |

SODIUM HYDROXIDE

| | | | | |
|-----------|-----------|--------|---------------------|-------|
| 215-185-5 | 1310-73-2 | C: R35 | Skin Corr. 1A: H314 | 1-10% |
|-----------|-----------|--------|---------------------|-------|

2-(2-BUTOXYETHOXY)ETHANOL

| | | | | |
|-----------|----------|---------|--------------------|-------|
| 203-961-6 | 112-34-5 | Xi: R36 | Eye Irrit. 2: H319 | 1-10% |
|-----------|----------|---------|--------------------|-------|

2-ETHYLHEXANOIC ACID

| | | | | |
|-----------|----------|---------|----------------|-------|
| 205-743-6 | 149-57-5 | Xn: R63 | Repr. 2: H361d | 1-10% |
|-----------|----------|---------|----------------|-------|

ALCOHOLS, C9-11, ETHOXYLATED

| | | | | |
|---|------------|------------------|--------------------------------------|-------|
| - | 68439-46-3 | Xn: R22; Xi: R41 | Acute Tox. 4: H302; Eye Dam. 1: H318 | 1-10% |
|---|------------|------------------|--------------------------------------|-------|

Section 4: First aid measures

[cont...]

SAFETY DATA SHEET

ECOFOAM ADVANCED

Page: 3

4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
- Eye contact:** Corneal burns may occur. May cause permanent damage.
- Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

[cont...]

SAFETY DATA SHEET

ECOFOAM ADVANCED

Page: 4

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): The identified uses for this product are detailed in Section 1.2

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

SODIUM HYDROXIDE

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|---------------------|------------|--------------|
| UK | - | 2 mg/m ³ | - | - |

2-(2-BUTOXYETHOXY)ETHANOL

| | | | | |
|----|------------------------|-------------------------|---|---|
| UK | 67.5 mg/m ³ | 101.2 mg/m ³ | - | - |
|----|------------------------|-------------------------|---|---|

DNEL/PNEC Values

DNEL / PNEC No data available.

[cont...]

SAFETY DATA SHEET

ECOFOAM ADVANCED

Page: 5

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Flammability limits %: lower: Not applicable.

upper: Not applicable.

Flash point°C: Not applicable.

Relative density: 1.05 – 1.15

pH: 11.8 – 12.8

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Acids. Zinc. Aluminium. Ammonia Solutions.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

[cont...]

SAFETY DATA SHEET

ECOFOAM ADVANCED

Page: 6

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM HYDROXIDE

| | | | | |
|-----|-----|------|-----|-------|
| IPR | MUS | LD50 | 40 | mg/kg |
| ORL | RBT | LDLO | 500 | mg/kg |

2-(2-BUTOXYETHOXY)ETHANOL

| | | | | |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 6050 | mg/kg |
| ORL | RAT | LD50 | 4500 | mg/kg |

2-ETHYLHEXANOIC ACID

| | | | | |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 3 | gm/kg |
| SKN | RBT | LD50 | 1260 | µl/kg |

ALCOHOLS, C9-11, ETHOXYLATED

| | | | | |
|--------|-----|------|-------------|-------|
| DERMAL | RAT | LD50 | 2000 - 5000 | mg/kg |
| ORAL | RAT | LD50 | 1200 | mg/kg |

Relevant effects for mixture:

| Effect | Route | Basis |
|-------------|-------------|-----------------------|
| Corrosivity | OPT INH DRM | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

ALCOHOLS, C9-11, ETHOXYLATED

| | | | |
|-------|-----------|----|------|
| ALGAE | 72H ErC50 | 47 | mg/l |
|-------|-----------|----|------|

[cont...]

SAFETY DATA SHEET

ECOFOAM ADVANCED

Page: 7

| | | | |
|---------|----------|-----------|------|
| DAPHNIA | 48H EC50 | 9 - 13.4 | mg/l |
| FISH | 96H LC50 | 11 - 23.7 | mg/l |

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1719

14.2. UN proper shipping name

Shipping name: CAUSTIC ALKALI LIQUID, N.O.S.
(SODIUM HYDROXIDE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

[cont...]

SAFETY DATA SHEET

ECOFOAM ADVANCED

Page: 8

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

This safety data sheet is prepared in accordance with Commission Regulation (EC) No 1272/2008.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H361d: Suspected of damaging the unborn child.

R22: Harmful if swallowed.

R35: Causes severe burns.

R36: Irritating to eyes.

R41: Risk of serious damage to eyes.

R63: Possible risk of harm to the unborn child.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Kilco (International) Ltd, Registered Office: 1A Trench Road, Mallusk,
Newtownabbey, Belfast, BT36 4TY. Place of Registration: Northern Ireland,
Registration Number: NI3240